Sure-Arc Welding Cable

- 30 gauge stranded copper wire
- Extra moisture-proof inner protection
- Tough neoprene jacket is resistant to oil, abrasion and impact
- Very flexible, even in subzero working conditions

Actual Wire Size with Neoprene Jacket

Cable Ga.	Number of Strands	Rated Intermittent Current	Feet Per Roll	Part No.	Pkg. Qty.
No. 4	420	100	25	**CW1322**	1
No. 4	420	100	50	**CW1323**	1
No. 2	665	200	25	**CW1324**	1
No. 2	665	200	50	**CW1325**	1
No. 1	836	250	25	**CW1326**	1
No. 1	836	250	50	**CW1327**	1
No. 1/0	1,064	300	50	**CW1328**	1
No. 1/0	1,064	300	100	**CW1329**	1
No. 2/0	1,310	375	100	**CW1331**	1

Cable Connectors

- Black universal connectors mate with most other brands
- The union of two Cronatron connectors insures maximum insulation

CW1303

CW1305

CW1359

Description	Cable Capacity	Part No.	Pkg. Qty.
Connector Set (CW1303 and CW1305)	1/0 to 3/0	**CW1304**	1 Set
Female Half	1/0 to 3/0	**CW1303**	1
Male Half	1/0 to 3/0	**CW1305**	1
Whip-Lead Connector	4 to 1	**CW1359***	1

**Whip-Lead Connector (CW1359) fits Female Half (CW1303)*

Electrode Holders

Medium Sized Aluminum Alloy Holder

- Ideal where weight is a factor
- One of the most popular holders available
- Will accommodate electrodes up to 1/4"

Medium Sized Copper Alloy Holder

- For maintenance and light production work
- 300A range for electrodes up to 1/4"

Low-Profile Copper Alloy Holder

- For maintenance, farm and all general welding
- Will accommodate electrodes up to 5/32"

Heavy-Duty Copper Alloy Holder

- Designed for continuous high amperage welding
- A must for molding or dual technique hardfacing applications
- Will accommodate electrodes up to 3/8"

Description	Amps	Length (Inches)	Weight (Oz.)	Part No.	Pkg. Qty.
Medium Sized Aluminum Alloy Holder	300	9-5/8	12	**CW1299**	1
Medium Sized Copper Alloy Holder	300	9-5/8	12	**CW1298**	1
Low Profile Copper Alloy Holder	200	8	12	**CW1297**	1
Heavy-Duty Copper Alloy Holder	500	12-3/4	30	**CW1598**	1

Twist Tight Gooseneck Electrode Holder

- Allows welders to deposit up to 20% more of each electrode as compared to tong-type holders
- Provides better visibility and maneuverability
- Greater hand-to-arc distance
- Higher electrode gripping pressure
- Quarter turn locks jaw tight on rod; turn back to release
- Will accommodate electrodes up to 1/4"

Amps	Length (Inches)	Weight (Oz.)	Part No.	Pkg. Qty.
400	8-1/2	16	**CW1579**	1